



# INTERIOR & EXTERIOR DOOR GUIDE

*Building Quality Doors Since 1866*



# SMOOTH FIBERGLASS DOORS



True 4 Panel

## *Durability to the Core*

When it comes to exterior protection, Steves fiberglass doors resist the elements beautifully. These smooth fiberglass doors won't dent, ding, rust, crack, split or warp. Plus, the insulating polystyrene core maintains U-factor for low-maintenance energy efficiency. It's the ideal choice for years of reliable value.

- Varying designs are available in smooth surfaces
- Closed-cell polystyrene core maintains U-factor and will not hold moisture
- 12" lock-block provides hardware reinforcement
- No cracking, splitting or warping
- Fiberglass skin is easy to paint
- PVC capped LVL stiles and top rail and composite bottom rail create an encapsulated product\*
- 25 year limited warranty

\*3'0" x 6'8" on all styles. Also on 2'6" x 6'8" and 2'8" x 6'8" six panel styles.

## Specifications

**Thickness:** 1-3/4"

**Door Widths:**

Flush: 2'0", 2'4", 2'6", 2'8", 2'10" and 3'0"

Embossed: 2'6"(narrow format 6P), 2'8", 2'10", 3'0"

**Door Heights:** 6'8" (all),

7'0" (NA)

8'0" (6P only)

**Custom Sizing:**

Custom sizes available in both widths and heights.

**Sidelite Widths:**

Flush: 1'0", 1'2", 1'4", 1'6", 1'8"

Embossed: 1/2 lite: 1'0", 1'2"

**Sidelite Heights:** 6'8" only

Retro sizes available

Primed smooth surfaces.

Expanded polystyrene (EPS) core.

Machining options available.

20 minute fire-rated construction available in most sizes (up to 8'0") and panel designs.

All door widths are 1/4" prefit and door heights are 3/4" or 1" prefit

All sidelites are book width.



6 Panel



4 Panel Blanktop



True 4 Panel



2 Panel Roundtop Plank\*



3 Panel Craftsman\*  
(utilizes 25" x 15-1/4" glass)



6 Panel Craftsman\*  
(utilizes 25" x 15-1/4" glass)

\* Available in 3068 only

### SIDELITE OPTIONS



Flush



1/2 Lite



Flush

# OAK TEXTURED FIBERGLASS PAINT-GRADE DOORS



## *Traditional Appeal with Weather-Resistant Performance*

Want a warmer, more traditional appearance than steel without sacrificing durability? Steves textured fiberglass doors are the answer. They're easy to paint and won't dent, ding or rust — providing low maintenance and energy efficiency.

- Varying designs are available in textured surfaces
- Closed-cell polystyrene core maintains U-factor and will not hold moisture
- 12" lock-block provides hardware reinforcement
- No cracking, splitting or warping
- Natural oak-grained surface
- PVC capped LVL stiles and top rail and composite bottom rail create an encapsulated product\*
- 25 year limited warranty

\*3'0" x 6'8" on all styles. Also on 2'8" x 6'8" flush and six panel styles.

3 Panel



Paintable oak-grained surface

# Specifications

**Thickness:** 1-3/4"

**Door Widths:**

Flush: 2'0", 2'4", 2'6", 2'8",  
2'10" and 3'0"  
Embossed: 2'8", 2'10", 3'0"

**Door Heights:** 6'8" (all),  
7'0" (NA)  
8'0" (Flush and 6P only)

**Custom Sizing:**

Custom sizes available in both widths  
and heights.

**Sidelite Widths:**

Flush: 1'0", 1'2", 1'4", 1'6", 1'8"  
Embossed: 1/2 and 3/4 lite: 1'0", 1'2"

**Sidelite Heights:** 6'8" only

Retro sizes available

White oak-grained textured surfaces.

Expanded polystyrene (EPS) core.

Machining options available.

20 minute fire-rated construction  
available in most sizes (up to 8'0")  
and panel designs.

All door widths are 1/4" prefit and  
door heights are 3/4" or 1" prefit

All sidelites are book width.



6 Panel



4 Panel Blanktop



True 4 Panel



3 Panel



Flush

**SIDELITE OPTIONS**



3/4 Lite



1/2 Lite



Flush